## NASA/TM-1999-209636



# A New Approach to Measure Contact Angle and Evaporation Rate With Flow Visualization in a Sessile Drop

Nengli Zhang Ohio Aerospace Institute, Brook Park, Ohio

David F. Chao Glenn Research Center, Cleveland, Ohio Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) Program Office plays a key part in helping NASA maintain this important role.

The NASA STI Program Office is operated by Langley Research Center, the Lead Center for NASA's scientific and technical information. The NASA STI Program Office provides access to the NASA STI Database, the largest collection of aeronautical and space science STI in the world. The Program Office is also NASA's institutional mechanism for disseminating the results of its research and development activities. These results are published by NASA in the NASA STI Report Series, which includes the following report types:

- TECHNICAL PUBLICATION. Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA's counterpart of peerreviewed formal professional papers but has less stringent limitations on manuscript length and extent of graphic presentations.
- TECHNICAL MEMORANDUM. Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- CONTRACTOR REPORT. Scientific and technical findings by NASA-sponsored contractors and grantees.

- CONFERENCE PUBLICATION. Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or cosponsored by NASA.
- SPECIAL PUBLICATION. Scientific, technical, or historical information from NASA programs, projects, and missions, often concerned with subjects having substantial public interest.
- TECHNICAL TRANSLATION. Englishlanguage translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services that complement the STI Program Office's diverse offerings include creating custom thesauri, building customized data bases, organizing and publishing research results . . . even providing videos.

For more information about the NASA STI Program Office, see the following:

- Access the NASA STI Program Home Page at http://www.sti.nasa.gov
- E-mail your question via the Internet to help@sti.nasa.gov
- Fax your question to the NASA Access Help Desk at (301) 621-0134
- Telephone the NASA Access Help Desk at (301) 621-0390
- Write to:

NASA Access Help Desk NASA Center for AeroSpace Information 7121 Standard Drive Hanover, MD 21076

### NASA/TM—1999-209636



# A New Approach to Measure Contact Angle and Evaporation Rate With Flow Visualization in a Sessile Drop

Nengli Zhang Ohio Aerospace Institute, Brook Park, Ohio

David F. Chao Glenn Research Center, Cleveland, Ohio

Prepared for the Interfaces for the Twenty-First Century: New Research Directions in Fluid Mechanics and Materials Science sponsored by the NASA OLMSA Microgravity Research Division, NSF Monterey, California, August 16–18, 1999

National Aeronautics and Space Administration

Glenn Research Center

Available from

## A NEW APPROACH TO MEASURE CONTACT ANGLE AND EVAPORATION RATE WITH FLOW VISUALIZATION IN A SESSILE DROP

Nengli Zhang and David F. Chao National Aeronautics and Space Administration Glenn Research Center Cleveland, Ohio 44135

The contact angle and the spreading process of sessile droplet are very crucial in many technological processes, such as painting and coating, material processing, film-cooling applications, lubrication, and boiling. Additionally, as it is well known that the surface free energy of polymers cannot be directly measured for their elastic and viscous restraints. The measurements of liquid contact angle on the polymer surfaces become extremely important to evaluate the surface free energy of polymers through indirect methods linked with the contact angle data.

Due to the occurrence of liquid evaporation is inevitable, the effects of evaporation on the contact angle and the spreading become very important for more complete understanding of these processes. Based on the laser shadowgraphic system used by the present author [1, 2], a very simple optical procedure has been developed to measure the contact angle, the spreading speed, the evaporation rate, and to visualize inside convection of a sessile drop simultaneously.

It is of interest to note that evaporation can induce Marangoni-Bénard convection in sessile drops [3]. However, the impacts of the inside convection on the wetting and spreading processes are not clear. The experimental methods used by previous investigators cannot simultaneously measure the spreading process and visualize the convection inside. The present work provides the solution for the first time.

The inside convection and the drop profile data can be synchronously recorded through the CCD camera I and II. CCD camera I would also precisely record the real-time diameter of the sessile drop which is essential for determination of both spreading speed and evaporation rate. As it is well known that a sessile drop takes the shape of a spherical cap provided its mass is sufficiently small, for example, less than 1 mg [4-6]. The sessile drop on the glass slide can be taken as a thin plano-convex lens with a focal length, f, which can be expressed as

$$f = \frac{R}{n-1} \tag{1}$$

where R is the curvature radius of the spherical cap, n is the refractive index of the liquid. By a simple geometric relationship as shown in Fig. 1,

$$f = \frac{d(s+p)}{d+D} \tag{2}$$

where d is the base diameter of the sessile drop, s is the distance from the center of the drop base to its image on the front surface of the mirror, p is the distance between images of the drop center on the mirror and on the screen, D is the diameter of the drop image on the screen. Both d and D are time dependent due to the spreading and the evaporation, which can be accurately measured through the direct photo-shadowgraphic system. It is obvious that as the function of time, the curvature radius of the liquid spherical cap can be then determined by the data of d and D:

$$R(t) = (n-1)(s+p)\frac{d(t)}{d(t) + D(t)}$$
(3)

The contact angle can be calculated as

$$\theta(t) = \arcsin \frac{d(t)}{2R(t)} \tag{4}$$

The evaporation rate can also be determined from the data of d and D. According to a simple geometric relationship, the instant volume of the sessile drop can be written as

$$V(t) = \pi h^{2}(t) [R(t) - \frac{h(t)}{3}]$$
 (5)




Figure 1.—Schematic of experimental setup.

Therefore, the evaporation rate is

$$\dot{V} = 2\pi h \dot{h} (R - \frac{h}{3}) + \pi h^2 (\dot{R} - \frac{\dot{h}}{3})$$
 (6)

where

$$h = R - \sqrt{R^2 - d^2/4} \,, \tag{7}$$

$$\dot{h} = \dot{R} - \frac{R\dot{R} - d\dot{d}/4}{\sqrt{R^2 - d^2/4}},$$
(8)

and

$$\dot{R} = (n-1)(s+p)\left[\frac{\dot{d}}{d+D} - \frac{d(\dot{d}+\dot{D})}{(d+D)^2}\right]$$
(9)

As an example, Figs. 2 and 3 show the direct photography from top and the laser shadowgraphy at moment t=4 sec., respectively, for an evaporating freon-113 sessile drop. Inside convection can be seen clearly in Fig.3.




Figure 2.—Direct photography from top. d(t) = 5.72 mm at t = 4 sec.




Figure 3.—Laser shadowgraphy. d(t) = 85.7 mm at t = 4 sec.

#### References

- 1. N. Zhang, and W.J. Yang, "Natural Convection in Evaporating Minute Drops," ASME Journal of Heat Transfer, vol. 104, pp. 656–662 (1982).
- 2. N. Zhang, and W.J. Yang, "Microstructure of Flow Inside Minute Drops Evaporating on a Surface," ASME Journal of Heat Transfer, vol. 105, pp. 908–910 (1983).
- 3. N. Zhang, and W.J. Yang, "Visualization of Evaporative Convection in Minute Drops by Laser Shadowgraphy," Rev. Sci. Instrum., vol. 54, no. 1, pp. 93–96 (1983).
- 4. R.G. Picknett, and R. Bexon, "The Evaporation of Sessile or Pendant Drops in Still Air," J. Colloid Interface Sci., vol. 61, no. 2, pp. 336–350 (1977).
- 5. S.M. Rowan, M.I. Newton, and G. McHale, "Evaporation of Microdroplets and the Wetting of Solid Surfaces," J. Phys. Chem., vol. 99, no. 35, pp. 13268–13271 (1995).
- 6. M.J. De Ruijter, J. De Coninck, and G. Oshanin, "Droplet Spreading: Partial Wetting Regime Revisited," Langmuir, vol. 15, no. 6, pp. 2209–2216 (1999).

### REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE	3. REPORT TYPE AND DATES COVERED
	December 1999	Technical Memorandum
4. TITLE AND SUBTITLE	5. FUNDING NUMBERS	
A New Approach to Measure C with Flow Visualization in a Se		
6. AUTHOR(S)	WU-101-13-0A-00	
Nengli Zhang and David F. Cha	ao	
7. PERFORMING ORGANIZATION NAME	8. PERFORMING ORGANIZATION REPORT NUMBER	
National Aeronautics and Space		
John H. Glenn Research Center	r at Lewis Field	E-11966
Cleveland, Ohio 44135–3191		
9. SPONSORING/MONITORING AGENCY	( NAME(S) AND ADDRESS(ES)	10. SPONSORING/MONITORING AGENCY REPORT NUMBER
National Aeronautics and Space	e Administration	
Washington, DC 20546-0001	NASA TM—1999-209636	
11. SUPPLEMENTARY NOTES		L
-	•	w Research Directions in Fluid Mechanics and Materials
		earch Division, NSF, Monterey, California, August 16–18,
		Point Road, Cleveland, Ohio 44142 (work funded under
		, NASA Glenn Research Center. Responsible person,
David F. Chao, organization co	* * *	
12a. DISTRIBUTION/AVAILABILITY STA	TEMENT	12b. DISTRIBUTION CODE
Unclassified - Unlimited		

Unclassified - Unlimited

Subject Categories: 25, 34, and 70 Distribution: Nonstandard

This publication is available from the NASA Center for AeroSpace Information, (301) 621-0390.

### 13. ABSTRACT (Maximum 200 words)

The contact angle and the spreading process of sessile droplet are very crucial in many technological processes, such as painting and coating, material processing, film-cooling applications, lubrication, and boiling. Additionally, as it is well known that the surface free energy of polymers cannot be directly measured for their elastic and viscous restraints. The measurements of liquid contact angle on the polymer surfaces become extremely important to evaluate the surface free energy of polymers through indirect methods linked with the contact angle data. Due to the occurrence of liquid evaporation is inevitable, the effects of evaporation on the contact angle and the spreading become very important for more complete understanding of these processes. It is of interest to note that evaporation can induce Marangoni-Bénard convection in sessile drops. However, the impacts of the inside convection on the wetting and spreading processes are not clear. The experimental methods used by previous investigators cannot simultaneously measure the spreading process and visualize the convection inside. Based on the laser shadowgraphic system used by the present author, a very simple optical procedure has been developed to measure the contact angle, the spreading speed, the evaporation rate, and to visualize inside convection of a sessile drop simultaneously. Two CCD cameras were used to synchronously record the real-time diameter of the sessile drop, which is essential for determination of both spreading speed and evaporation rate, and the shadowgraphic image magnified by the sessile drop acting as a thin plano-convex lens. From the shadowgraph, the inside convection of the drop can be observed if any and the image outer diameter, which linked to the drop profile, can be measured. Simple equations have been derived to calculate the drop profile, including the instantaneous contact angle, height, and volume of the sessile drop, as well as the evaporation rate. The influence of the inside convection on the wetting and spreadi

14. SUBJECT TERMS	15. NUMBER OF PAGES		
Spreading; Contact angle; Evaporation rate; Flow visualization			16. PRICE CODE
	A02		
17. SECURITY CLASSIFICATION OF REPORT	18. SECURITY CLASSIFICATION OF THIS PAGE	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT
Unclassified	Unclassified	Unclassified	